

NK RAPTOR SPIKES & TOPSPIKE



NK ANTI-VANDAL

RAPTOR SPIKES GENERAL SPECIFICATIONS

SPINNER UNITS: Colour coated impact resistant Nylon. Raptor spikes offer a maximum impaling projection of 50mm.

SUPPORT BRACKETS: Mild steel brackets manufactured using 40 x 6mm flat bar fixed at 1.32m centres.

AXLE: Raptor units mounted on 16mm diameter galvanised mild steel axle rail, complete with Raptor washers.

FINISH: This system is available in a wide range of colours to match either fencing systems or Company Corporate colours.

KEY FEATURES: A robust device, both powerful and as a visual deterrent, impressive in appearance. Extremely versatile, Raptor can be fitted to fences, walls, gates, roof elevations, CCTV Masts etc. The 220mm Raptor units offer a unique anti-scaling deterrent to would-be intruders.

TOPSPIKE GENERAL SPECIFICATIONS

SPINNER UNITS: Mild steel anti-truder device 156mm long x 380mm diameter constructed 25mm RHS spindle with 10mm square bar projecting spikes.

SUPPORT BRACKETS: Mild steel brackets 40 x 6mm flat bar or 40 x 40mm RSA brackets fixed at 936mm centres.

AXLE: Continuous 16mm diameter mild steel axle rod.

FINISH: This system is available galvanised and polyester powder coated to BS EN 13438-2005 in a wide range of colours to match either fencing systems or Company Corporate colours.

KEY FEATURES: NK Topspike has a robust distinctive appearance suitable for use over fences, walls, roof elevations etc. The free rotation spinner units render climbing or scaling extremely difficult.

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019