



NK IBEX

GENERAL SPECIFICATIONS

POST SYSTEM: RHS at 2.950m centres, panel fixed to posts with 25 x 5mm slotted clamp bar using NK M8 tamper-resistant bolt and threaded nutserts.

PANEL WIDTH: 3005mm

MESH APERTURE: 200 x 50mm

WIRE DIAMETER: 6mm horizontal, 5mm vertical.

FINISH: Galvanised and polyester powder coated to BS EN 13438-2005 in a range of colours to suit your individual requirements.

FENCE Ht (m)	POST SECTION	NUMBER OF FOLDS	NUMBER OF FIXINGS
1.2	60x60	2	4
1.85	60x60	4	5
2.05	60x60	4	6
2.45*	60x60	4	7
3.05*	60x60	6	9

* Multi-lift panels - 1.85 with 1.2 above. # With protruding wires

APPLICATION: NK Ibx Premier Plus is a general purpose fencing system for boundary demarcation and aesthetic perimeters, where increased resistance to breaching is desired. Widely used in the commercial and housing construction sectors by building contractors.

KEY FEATURES: NK Ibx Premier Plus is constructed from folded rigid mesh panels with 6mm horizontal and 5mm vertical wires, securely fixed to posts at multiple points using NK clamping bars. Panel heights greater than 2.05m offer 22mm protruding wire ends on the top edge to provide an increased security enhancement.

Installation of all fencing is subject to site specific risk assessments and NK recommends due regard should be given to nearby aids to scaling or natural overhangs.

RELATED PRODUCTS

SWINGING AND SLIDING GATES: Single and Double Leaf Swinging and Sliding Gates are available in a range of standard widths to suit your individual requirements, with manual or with automated control.

OTHER PRODUCTS:

- ▶ NK Ibx Vogue
- ▶ NK Ibx Elite
- ▶ NK Ibx Supreme
- ▶ NK Ibx Security
- ▶ NK Ibx Hi-Security
- ▶ NK Ibx Premier

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019