



NK IBEX

* Inverted panel configuration shown

GENERAL SPECIFICATIONS

POST SYSTEM: RHS at 2.523m centres, panel fixed to posts with type 006 and 007 clips using NK M8 tamper-resistant bolt with threaded nutserts.

PANEL WIDTH: 2506mm

MESH APERTURE: 200 x 50mm

WIRE DIAMETER: 8mm horizontal, 6mm vertical.

FINISH: Galvanised and polyester powder coated to BS EN 13438-2005 in a range of colours to suit your individual requirements.

| FENCE Ht (m) | POST SECTIONS RHS | NUMBER OF FIXINGS |
|--------------|-------------------|-------------------|
| 1.2 | 60x60 | 4 |
| 2.0 | 60x60 | 6 |
| 2.4 | 60x60 | 7 |
| 3.0 | 80x80 | 9 |

APPLICATION: NK Ibox Supreme 868 is a heavy duty rigid mesh fencing system for boundary demarcation and aesthetic perimeters where increased security and resilience to damage is needed. NK Ibox Supreme 868 is a popular choice for industrial centres, commercial premises and business parks.

KEY FEATURES: NK Ibox Supreme 868 is constructed from a heavy duty rigid mesh panel with a 200mm x 50mm mesh aperture having thick horizontal wires 8.0mm diameter and single vertical wire 6.0mm diameter. Panels offer 22mm protruding wire ends on the top edge to provide an increased security enhancement.

Installation of all fencing is subject to site specific risk assessments and for heights less than 2m, NK recommends the panels are installed with the protruding wire ends pointing down and embedded.

RELATED PRODUCTS

SWINGING AND SLIDING GATES: Single and Double Leaf Swinging and Sliding Gates are available in a range of standard widths to suit your individual requirements, with manual or with automated control.

OTHER PRODUCTS:

- ▶ NK Ibox Vogue
- ▶ NK Ibox Elite
- ▶ NK Ibox Premier
- ▶ NK Ibox Premier Plus
- ▶ NK Ibox Security
- ▶ NK Ibox Hi-Security

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019