



NK SALVUS

GENERAL SPECIFICATIONS

HEIGHT: 1200mm above ground level

FITTINGS: NK adjustable hinges and NK Hasp and Staple Locking Mechanism.

FINISH: Galvanised and polyester powder coated to BS EN 13438-2005 in a range of colours to suit your individual requirements.

COMPONENT PARTS	SINGLE LEAF 7m OPENING	DOUBLE LEAF 10m OPENING
HANGING POST SECTION	200x200mm RHS	150x150mm RHS
FRAME SECTION	100x60mm RHS	100x50mm RHS
SUPPORT POSTS	100x100mm RHS	100x100mm RHS

KEY FEATURES: An alternative solution to control vehicular access when traffic flow is limited to short intensive periods. The swinging barrier can be locked in both the open and closed positions. A strong physical vehicular access deterrent.

RELATED PRODUCTS



NK Salvus Rising Barriers are a compact automated access control solution offering cost effective vehicular management with ease of operation.

OTHER PRODUCTS:

- ▶ NK Salvus Cantilever Gates
- ▶ NK Salvus Automated Swinging Gates
- ▶ NK Salvus Turnstiles
- ▶ NK Salvus Self-Closing Safety Gates
- ▶ NK Salvus Bollards

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019